



राष्ट्रीय प्रौद्योगिकी संस्थान अगरतला

NATIONAL INSTITUTE OF TECHNOLOGY AGARTALA
Barjala, Jirania, P.O. – NIT Agartala, Pin – 799045, West Tripura
Phone : 0381 2346 630/ 629, Fax : 0381 2346 360
Website : [http:// www.nita.ac.in](http://www.nita.ac.in)

Notice Inviting Quotation

F.23(382)/NITA/Estate/2025/ 8335-39

Date: 08.12.2025

Sealed quotations are invited for and on behalf of NIT Agartala, from registered Contractors of appropriate class for the work as per following tables:

Sl. No	Name of Work	Time of Completion	Last Date of Submission of quotation	Date of Opening (If possible)
1	Construction of Canopy with MS truss and sheet for Post Office entrance and providing and fixing of MS post for existing RCC canopy for entrance of SBI Canara bank and corridor in KV building at NIT Agartala	60 days	01-01-2026 (upto 3:00 pm)	02-01-2026 (3:30 pm)

Quotation would be submitted on item rate basis as per schedule of work attached. The details regarding quotation would be available in the institute website and may be downloaded and submitted in the form of hard copy to office of the Estate Section, NIT Agartala on before ...01.01.2026 upto 3:00 PM. The same may also be available in the Estate Section of NIT Agartala. The quotation will not be accepted other than hard copy.

The complete set of quotation should be properly addressed and submitted in sealed envelope. For any enquiry, please contact by email to estate.civil@mail.nita.ac.in on before the last date of submission of quotation.

Enclo. 1. BOQ of the work

2. Terms & condition for specification of quotation.

(SIGNATURE)

Registrar, NIT Agartala

Copy to:

1. The P.S. to the Director for kind information.
2. The Dean (P&D) for kind information.
3. The Head (F&A), NITA.
4. The Estate Engineer for kind information and necessary action
5. Mr. Kamal Kanti Paul, System Administrator, NIT Agartala with request for launching of this NIT in the website: <http://www.nita.ac.in>

Registrar, NIT Agartala

TERMS & CONDITIONS FOR SUBMISSION OF QUOTATION FOR SUPPLY OF STORES ORDERED

1. **Rate:** The rate quoted must be net inclusive of packing, forwarding, freight, and all other incidental charges. The risk of damage or loss in transit if any will be the suppliers. All taxes and duties (as per rules) are inclusive.
2. **Delivery:** Central Store at NIT Agartala Campus by Supplier or Registered Transport under sale tax department of Govt. of Tripura.
3. All formalities for road permit and tax clearance should be completed by the Supplier. NIT Agartala will not take any responsibility for arranging road permit/tax clearance and shall not take any responsibility for any delay for delivery at NIT Agartala.
4. **Period of completion:** Within **60 days** from the date of receipt of the purchase/work order.
5. **Invoice:** Invoice/Bill/Challan indicating the product serial number should be raised in the name of the Registrar, NIT Agartala.
6. **Liquidated damage:** - For late delivery, Liquidated damages at 0.5% per week in respect of the total contract value.
7. NITA is registered with the Department of Scientific and Industrial Research(DSIR), Government of India for the purpose of availing Customs Duty exemption vide No.TU/V/RG-CDE(1053)/2017 dated 15.03.2018. If it is required subsequently, NITA may provide relevant exemption certificate as per request of the supplier.
8. **Terms of payment:** 100% will be made against successful supply & inspection.
9. For any enquiry, please contact with Estate Engineer.
10. **All disputes/ Arbitration:** All disputes should be attempted to resolve mutually between the NIT Agartala and the supplier through discussion and arbitration. The Arbitrator shall be appointed by the Director, NIT Agartala. Failing which, all disputes shall be under the jurisdiction of Courts at Agartala only.
11. **Warranty:** The quotation must contain the terms of warranty, and extended warranty, if available.
12. **Submission of Quotation:** All quotations must be forwarded in sealed cover addressed to the authority mentioned pre-page, so as to reach within the specified period. The reference to the Enquiry No. and the last date for submission must clearly be super-scribed on the sealed envelope.
13. **Opening of Quotation:** Every quotation will be opened at the office of the concerned Department/Centre, NIT, Agartala at the time on the tender form. A firm may send its accredited representative to witness the opening if it so desires.
14. **Period of Validity:** A quotation shall remain valid for acceptance at least for a period of 60 days from the date of opening.
15. **Rejection of Offers:** The Institute reserves the right to ignore or reject any offer including the lowest one without assigning any reason.
16. **For technical details, please contact:**

Estate Engineer

Estate Section

Email : estatesectioncivil@gmail.com

Name of work: Construction of Canopy with MS truss and sheet for Post Office entrance and providing and fixing of MS post for existing RCC canopy for entrance of SBI Canara bank and corridor in KV building at NIT Agartala

Name of Contractor:

#	Description of Items	Qty	Unit	Rate	Amount
1	Providing and fixing expansion hold fasteners on C.C. /R.C.C./Brick masonry surface backing including drilling necessary holes and the cost of bolt etc complete. Wedge expansion type Fastener with threaded dia 10 mm	64.000	each		
2	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes	480.197	kg		
3	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : One or more coats on old work	13.876	sqm		
4	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	10.508	sqm		
5	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete :				
5.1	Ridges plain (500 - 600mm)	2.250	metre		
6	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge.	0.108	cum		
7	15 mm cement plaster on the rough side of single or half brick wall of mix : 1:4 (1 cement: 4 fine sand)	0.720	sqm		
Total Amount (Rs.)=					
Total Amount In words:					

Specification

#	Description of Items	NO	L	B	D	Co-ef	Qty	Unit
1	Providing and fixing expansion hold fasteners on C.C./R.C.C./Brick masonry surface backing including drilling necessary holes and the cost of bolt etc complete. Wedge expansion type Fastener with threaded dia 10 mm							
	Post	6 x 8					48.000	each
		4 x 4					16.000	each
							64.000	each
2	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished welded type tubes							
	Post	8 x 1	2.5			7.93	158.600	kg
		2 x 1	3			7.93	47.580	kg
	truss	2 x 1	3.6			4.37	31.464	kg
		4 x 1	2.232			4.37	39.015	kg
		6 x 1	0.553			4.37	14.500	kg
		6 x 1	2.15			4.37	56.373	kg
		8 x 2	0.3	0.3		78.5	113.040	sqm
		2 x 2	0.25	0.25		78.5	19.625	sqm
							480.197	kg
3	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : One or more coats on old work							
	Post	8 x 1	2.5			0.241	4.820	sqm
		2 x 1	3			0.241	1.446	sqm
	truss	2 x 1	3.6			0.153	1.102	sqm
		4 x 1	2.232			0.153	1.366	sqm
		6 x 1	0.553			0.153	0.508	sqm
		6 x 1	2.15			0.153	1.974	sqm
		12 x 2	0.3	0.3			2.160	sqm
		4 x 2	0.25	0.25			0.500	sqm
							13.876	sqm
4	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineerin-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.							
		1 x 2	2.25	2.34			10.508	sqm
							10.508	sqm

5	Providing and fixing pre-coated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete :								
5.1	Ridges plain (500 - 600mm)	1 x	1	2.25					
								2.250	metre
								2.250	metre
6	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in-charge.								
		1 x	1	3.6	0.2	0.15		0.108	cum
								0.108	cum
7	15 mm cement plaster on the rough side of single or half brick wall of mix : 1:4 (1 cement: 4 fine sand)								
		1 x	1	3.6	0.2			0.720	sqm
								0.720	sqm

